

NEW!

Stand-alone CompX eLock



Note: temperature probe cable is longer than shown.

Access Control only:

- ◆ New ergonomic design
- ◆ 3,000 users/supervisors codes
- ◆ LockView software provides an Audit Trail of the last 15,000 access attempts; including date, time and user name via USB connection
- ◆ New membrane keypad provides durability and ease of cleaning
- ◆ Three modes of access: Keypad, Proximity card* (HID), Magstripe card* (Track 2)
**Use existing identification cards*
- ◆ Motor driven latching mechanism provides the convenience of automatic relocking
- ◆ Removable battery pack (6 AA batteries, not included) for simplified battery maintenance
- ◆ Complies with Joint Commission standards and is 21 CFR Part 11 compliant

Access Control with Temperature Monitoring:

- ◆ Monitors internal temperature 100°C to -100°C
- ◆ Programming can be done manually on user friendly LCD blue backlit screen or through LockView® software
- ◆ Provides programmable charts, graphs, reports (LockView® function)
- ◆ Records up to 500,000 temperature data points
- ◆ Audible and visual local alarming at eLock

CompX
SECURITY PRODUCTS

Reorder #: F2644-028

Copyright 2010 © CompX Security Products / 847.752.2500 / compx.com / 715 Center St., Grayslake, IL 60030
Any companies and/or products referred to herein are marks or registered trademarks of their respective companies, owners and/or mark holders.

For more information, call **847.752.2500**